



Höhe mm	(B) Breite		(NA) Nabenabstand		Wärmeleistung		Wasser- inhalt Liter	Heizpatrone empfohlen Watt	(A1=A2) Wandabstand		(A3) gebogen mm
	gerade mm	gebogen mm	gerade mm	gebogen mm	75/65/ 20° Watt	55/45 20° Watt			gerade mm	gebogen mm	
944	450	443	400	393	402	218	3,9	300	65-85	59-79	290
944	500	495	450	445	439	237	4,2	300	65-85	54-74	295
944	600	593	550	543	513	276	4,7	600	65-85	57-77	436
944	750	737	700	687	624	332	5,6	600	65-85	52-72	580
1322	450	443	400	393	552	296	5,4	600	65-85	59-79	290
1322	500	495	450	445	603	324	5,8	600	65-85	54-74	295
1322	600	593	550	543	703	377	6,6	600	65-85	57-77	436
1322	750	737	700	687	854	456	7,8	800	65-85	52-72	580
1658	450	443	400	393	682	363	6,8	600	65-85	59-79	290
1658	500	495	450	445	745	397	7,2	800	65-85	54-74	295
1658	600	593	550	546	871	466	8,2	800	65-85	57-77	436
1658	750	737	700	687	1061	569	9,7	1000	65-85	52-72	580
1868	450	443	400	393	762	408	7,5	800	65-85	59-79	290
1868	500	495	450	445	833	446	8,0	800	65-85	54-74	295
1868	600	593	550	543	976	523	9,1	1000	65-85	57-77	436
1868	750	737	700	687	1191	637	10,7	1000	65-85	52-72	580